

### AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A voltage regulator comprising:  
an input stage having a first input, a second input, and an output;  
a reference voltage circuit coupled to said first input;  
an output stage coupled to said second input; and  
a gain stage comprising a buffer device and a drive circuit, said buffer device  
coupled to said output of said input stage and said drive circuit, said drive circuit coupled  
to said output stage, said drive circuit comprising:  
a first transistor coupled to said output stage;  
a base current translation circuit; and  
a current divide circuit coupled to the first transistor and to said base  
current translation circuit, wherein said current divide circuit is operable to deliver  
a portion of a first current of said first transistor to said base current translation  
circuit; and  
wherein said base current translation circuit is operable to deliver to the  
base of said first transistor a second current;  
wherein said buffer device is operable to provide isolation between said input  
stage and said drive circuit.
2. (Original) The voltage regulator of Claim 1, wherein said drive circuit comprises a  
field effect transistor.
3. (Cancelled)

Serial No.: ~~10/755,528~~

10/775,528

- 2 -

Examiner: Sterrett, Jeffrey L.

Art Unit: 2838

4. (Currently Amended) The voltage regulator of ~~Claim 3~~ Claim 1, wherein said second current is greater in magnitude than a base current of the first transistor.
5. (Original) The voltage regulator of Claim 1, further comprising a capacitor coupled to said buffer device and said input stage, and wherein said buffer device comprises a beta of approximately at least 1000.
6. (Currently Amended) The voltage regulator of Claim 1, further comprising:  
an ~~impedence~~ impedance coupled to said second input of the input stage and to said output stage; and  
a device coupled to said input stage to provide a substantially constant bias current for said input stage, wherein output dependent current loading effects through said impedance are avoided.
7. (Original) The voltage regulator of Claim 1, further comprising a proportional to absolute temperature circuit coupled to said input stage and said gain stage and operable to provide a biasing current that is substantially independent of temperature.
8. (Currently Amended) A low dropout voltage regulation circuit comprising:  
an input comparison stage having an inverting input, a non-inverting input, and an output, said inverting input coupled to an output voltage node;  
a bandgap reference voltage circuit coupled to said non-inverting input;

a low dropout output stage coupled to an input voltage node and the output voltage node; and

a gain stage comprising a buffer device and a drive circuit, said buffer device coupled to said output of said input stage and said drive circuit, said drive circuit coupled to said output stage, said drive circuit comprising

a first transistor coupled to said output stage;

a base current translation circuit; and

a current divide circuit coupled to the first transistor and to said base current translation circuit, wherein said current divide circuit is operable to deliver a portion of a first current of said first transistor to said base current translation circuit; and

wherein said base current translation circuit is operable to deliver to the base of said first transistor a second current that is greater in magnitude than a base current of the first transistor;

wherein said buffer device is operable to provide isolation between said input stage and said drive circuit.

9. (Original) The regulation circuit of Claim 8, wherein said buffer device comprises a pnp transistor.

10. (Cancelled)

Serial No.: ~~10/755,528~~

10/775,528

- 4 -

Examiner: Sterrett, Jeffrey L.  
Art Unit: 2838

11. (Original) The voltage regulator of Claim 8, wherein said drive circuit comprises a field effect transistor.

12. (Original) The voltage regulator of Claim 8, further comprising:  
an impedance coupled to said inverting input of the input comparison stage and to said output stage; and  
a transistor coupled to said input comparison stage to provide a substantially constant bias current for said input stage, wherein output dependent current loading effects through said impedance are avoided.

13. (Original) The voltage regulator of Claim 8, further comprising:  
a biasing device coupled to said input comparison stage and to said output stage, wherein said biasing device is configured to provide a bias current to said input stage that is logarithmically related to an output current of said output stage.

14. (Original) The voltage regulator of Claim 8, further comprising:  
a biasing device coupled to said input comparison stage and to said output stage, wherein said biasing device is configured to provide a bias current to said input stage that is linearly proportional to an output current of said output stage.

15. (Currently Amended) A voltage regulation circuit comprising:  
an input comparison stage comprising a first pnp transistor and a second pnp transistor, said first pnp transistor coupled to an output voltage node;

Serial No.: ~~10/755,528~~

10/775,528

- 5 -

Examiner: Sterrett, Jeffrey L.  
Art Unit: 2838

a bandgap reference voltage circuit coupled to said second pnp transistor;  
an output stage coupled to an input voltage node and the output voltage node; and  
a gain stage ~~comprising~~ comprising:

a third pnp transistor ~~and a drive transistor, said third pnp transistor~~  
coupled to said output of said input stage; ~~and said drive transistor, said~~

a drive transistor coupled to said third pnp transistor and said output  
~~device; device;~~

mirror transistors coupled to said drive transistor; and

a translation circuit coupled to the mirror transistors;

wherein the mirror transistors are operable to deliver a portion of a first  
current of said drive transistor to said translation circuit; and

wherein said translation circuit is operable to deliver to the base of said  
drive transistor a second current that is greater in magnitude than a base current of  
said drive transistor.

16. (Cancelled)

17. (Currently Amended) The voltage regulation circuit of ~~Claim 16~~ Claim 15,  
wherein said translation circuit comprises a first translation transistor coupled to the  
mirror transistors and a second translation transistor coupled to the base of the drive  
transistor.

Serial No.: ~~10/755,528~~

10/775,528

- 6 -

Examiner: Sterrett, Jeffrey L.  
Art Unit: 2838

18. (Original) The voltage regulator of Claim 17, further comprising a pnp cascode transistor having a base coupled to said first translation transistor and an emitter coupled to said second translation transistor.
19. (Original) The voltage regulator of Claim 15, wherein said third pnp transistor is configured as a substantially unity gain buffer.
20. (Original) The voltage regulator of Claim 15, further comprising:  
an impedance coupled to said first pnp transistor and to said output voltage node;  
and  
a biasing transistor coupled to said input comparison stage to provide a substantially constant bias current for said input stage, wherein output dependent current loading effects through said impedance are avoided.
21. (Original) The voltage regulator of Claim 15, further comprising a proportional to absolute temperature circuit coupled to said input stage and said gain stage and operable to provide a biasing current that is substantially independent of temperature.